


REV.	DESCRIPTION	DATE	APPROVED
1.0	INITIAL RELEASE.	10/31/2014	J. SHEARER



CABLE PINOUT		
MOLEX PIN	WIRE	FUNCTION
1	RED	V IN (+)
2	BLUE	V AUX (+) (KEEP-ALIVE)
3	BROWN	REGEN (+)
4	BLACK	V IN (-)
5	WHITE	V AUX (-) (KEEP-ALIVE)
6	GREEN	REGEN (-)

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	42-2107	Conn, Molex Part No. 39-01-2065, Mini-Fit Jr Receptacle, Dual Row, 6 Circuits	1
2	42-2108	Conn, Molex Part No. 39-00-0207, Mini-Fit Female Crimp Terminal, 18-24 AWG	6
3	40-2012	Multi-Conductor Cable, 18 AWG, 6 Conductor, Shielded	1
4	40-2013-1	Heatshrink Tubing, 1/4" Diameter, Polyolefin, Black	1
5	40-2014-1	Heatshrink Tubing, 1/4" Diameter, Polyolefin, Clear	1
6	32-0121	Finished Goods Label, AC-CB-100121	1

UNLESS OTHERWISE SPECIFIED:
INTERPRET PER ASME Y14.5-1994
DIMENSIONS ARE IN INCHES
APPLY TOL AFTER FINISH
.XX ± .01
.XXX ± .005
X° ± 1°

ALL SURFACES: 
REMOVE ALL SHARP EDGES
R .01 OR CHAMFER MAX

APPROVAL	DATE
DRB: J. SHEARER	10/24/2014
APVD: C. LAMENDOLA	10/24/2014
PROPRIETARY THIS DRAWING IS THE PROPERTY OF ALLIED MOTION TECHNOLOGIES, INC. THE REPRODUCTION, DISTRIBUTION, AND UTILIZATION OF THIS DOCUMENT WITHOUT WRITTEN AUTHORIZATION IS PROHIBITED.	

 495 COMMERCE DR, STE 3
AMHERST, NY 14228-2313

TITLE: 15A SXC/SXD, Power Cable, 3m Length		
DWG NO: AC-CB-100121	REV: 1.0	
SIZE B	DO NOT SCALE	SHEET 1 OF 1