


REV.	DESCRIPTION	DATE	APPROVED
1.0	INITIAL RELEASE.	10/31/2014	J. SHEARER




CABLE PINOUT		
MOLEX PIN	WIRE	FUNCTION
1	RED	PHASE A
2	WHITE	PHASE B
3	BLACK	PHASE C
4	GREEN	CHASSIS

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	42-2106	Conn, Molex Part No. 39-01-4040, Mini-Fit Jr Receptacle, Single Row, 4 Circuits	1
2	42-2108	Conn, Molex Part No. 39-00-0207, Mini-Fit Female Crimp Terminal, 18-24 AWG	4
3	40-2011	Multi-Conductor Cable, 18 AWG, 4 Conductor, Shielded	1
4	40-2013-2	Heatshrink Tubing, 3/8" Diameter, Polyolefin, Black	1
5	40-2014-2	Heatshrink Tubing, 3/8" Diameter, Polyolefin, Clear	1
6	32-0124	Finished Goods Label, AC-CB-100124	1

UNLESS OTHERWISE SPECIFIED:
INTERPRET PER ASME Y14.5-1994
DIMENSIONS ARE IN INCHES
APPLY TOL AFTER FINISH
.XX ± .01
.XXX ± .005
X° ± 1°

ALL SURFACES: 
REMOVE ALL SHARP EDGES
R .01 OR CHAMFER MAX

APPROVAL	DATE
DRB: J. SHEARER	10/24/2014
APVD: C. LAMENDOLA	10/24/2014
PROPRIETARY THIS DRAWING IS THE PROPERTY OF ALLIED MOTION TECHNOLOGIES, INC. THE REPRODUCTION, DISTRIBUTION, AND UTILIZATION OF THIS DOCUMENT WITHOUT WRITTEN AUTHORIZATION IS PROHIBITED.	



495 COMMERCE DR, STE 3
AMHERST, NY 14228-2313

TITLE:
MXC, Motor Cable, 3m Length

DWG NO:
AC-CB-100124

REV:
1.0

SIZE BDO NOT SCALESHEET 1 OF 1